

# EC Material Safety Data Sheet

Manufacturer/Supplier: Vandex Isoliermittel-Gesellschaft mbH, D-21493 Schwarzenbek  
Product number: 032  
Trade name: VANDEX ANTI SULPHATE  
Printing date: 01. 08. 2006

Reviewed on: 01. 08. 2006

Page: 1/4

## 01. Identification of preparation and company

### Trade name

VANDEX ANTI SULPHATE

### \* Use of preparation

Anti sulphate agent for render

### Manufacturer/Supplier

Vandex Isoliermittel-Gesellschaft m.b.H.

Industriestrasse 19-23

D-21493 Schwarzenbek

Phone: +49 4151 89 15-0

Fax: +49 4151 89 15 50

### \* General Information

Phone: +49 41 51 89 15 31 (Laboratory, Vandex Isoliermittel GmbH, Germany)

Phone: +41 32 626 36 36 (Technical Department, Vandex International AG, Switzerland)

### \* Emergency telephone

GIZ Nord Poisons Centre, Germany

Phone: +49 551 19240

## 02. Composition/Information on ingredients

### \* Chemical characterization

Cement preparation

### \* Hazardous ingredients

Ingredients	CAS no.	EINECS no.	Concentration	Hazard symbols	R-phrases
Cement ( $\leq 2$ ppm CrVI)	65997-15-1	266-043-4	75-100%	Xi, irritant	R 38, 41
Barium chloride dihydrate	10326-27-9	233-788-1	< 3%	T, toxic	R 20, 25

## 03. Hazards identification

### \* Classification

Xi irritant

R 38 Irritating to skin.

R 41 Risk of serious damage to eyes.

### \* Particular information pertaining specific risk for humans and environment

Prolonged contact with the product may cause skin disorders / chemicals burns

### \* Further information

The content of hexavalent chromium in the cement is reduced to  $\leq 2$  ppm. The chromate reduction is effective within the shelf life and when properly stored. Please refer to chapter 7.

## 04. First aid measures

### \* Inhalation

Remove person from exposure. In case of irritation of respiratory system seek medical advice.

### Skin contact

After contact with skin wash immediately with plenty of water. If irritation persists seek medical advice.

### \* Eye contact

In case of contact with the eyes rinse immediately with plenty of water (eye lid wide open) for at least 10 minutes and seek medical advice urgently.

### Ingestion

Drink plenty of water. Seek medical advice.

## 05. Fire-fighting measures

### \* Suitable extinguishing media

Adapt to surrounding fire; product is not combustible.

### \* Special exposure hazards arising from the preparation itself, combustion products, resulting gases

Avoid extinguishing water entering into water courses, drains or ground water.

In contact with extinguishing water an alkaline solution – which can cause irritation – is produced.

### \* Special protective equipment for fire-fighters

Use self-contained breathing apparatus

## EC Material Safety Data Sheet

Manufacturer/Supplier: Vandex Isoliermittel-Gesellschaft mbH, D-21493 Schwarzenbek  
Product number: 032  
Trade name: VANDEX ANTI SULPHATE  
Printing date: 01. 08. 2006

Reviewed on: 01. 08. 2006

Page: 2/4

### 06. Accidental release measures

#### \* Personal precautions

Avoid contact with skin and eyes. Do not breathe dust. Refer to chapter 8.

#### Environmental precautions

Avoid uncontrolled contact with water. Avoid uncontrolled discharge into environment after contact with water. Do not allow to enter into water courses, drains or ground water.

#### Methods for cleaning up/collecting

Clean up dry. Avoid dust formation.

### 07. Handling and storage

#### \* Information for safe handling

Keep out of the reach of children.

Avoid dust formation and dust deposit.

Avoid contact with skin and eyes.

Do not breathe dust.

Refer to chapter 8 – Personal protective equipment

#### Information about protection against explosions and fires

Not applicable.

#### \* Requirements to be met by storerooms and containers

Store protected from humidity in unopened, undamaged original packaging. Shelf life: 12 months

#### \* Information about separation of incompatible products

Keep away from food, drink and animal feedingstuffs.

### 08. Exposure controls and personal protection

#### \* Exposure limit values (Great Britain)

65997-15-1	Portland cement inhalable dust respirable dust	EH40 / 2005: OEL 8-hour TWA EH40 / 2005: OEL 8-hour TWA	10 4	mg/m <sup>3</sup> mg/m <sup>3</sup>
–	Barium compounds soluble (as Ba)	EH40 / 2005: OEL 8-hour TWA	0.5	mg/m <sup>3</sup>

OEL = Occupational Exposure Limit; TWA = Time Weighted Average; Observe country specific occupational exposure limits

#### \* Occupational exposure controls

Avoid dust formation. Avoid creating dust. Provide appropriate ventilation or local exhaust ventilation. If it is not possible to reduce exposure levels to below exposure limit values with ventilation use appropriate respirator according to national regulations.

#### \* Personal protective equipment

General protective and hygiene measures

Do not eat or drink during work – no smoking. Wash hands before breaks and after work. Use appropriate skin protection products.

#### \* Respiratory protection

Use approved dust mask/respirator

#### \* Hand protection

Use suitable impervious protective gloves

#### Eye protection

Use tightly fitting safety glasses.

#### \* Skin protection

To avoid skin contact use suitable protective clothing.

#### \* Environmental exposure controls

Do not allow to enter into water courses, drains or ground water.

### 09. Physical and chemical properties

#### \* General information

Appearance: grey powder

Odour: odourless

#### \* Important health, safety and environmental information

Boiling point: not applicable

Flashpoint: not applicable

Ignition temperature: not applicable

Explosive limits:

Lower/Upper: not applicable

Vapour pressure: not applicable

Bulk density: approx. 1.45 kg/l

# EC Material Safety Data Sheet

Manufacturer/Supplier: Vandex Isoliermittel-Gesellschaft mbH, D-21493 Schwarzenbek  
Product number: 032  
Trade name: VANDEX ANTI SULPHATE  
Printing date: 01. 08. 2006

Reviewed on: 01. 08. 2006

Page: 3/4

Solubility in water: (20 °C) up to 1.5 g/l  
pH-value: 11 – 13.5

## 10. Stability and reactivity

### Conditions to avoid

Avoid contact with humidity.

### \* Materials to avoid

Acid

### \* Hazardous decomposition products

Not applicable.

## 11. Toxicological information

### \* Irritant/Corrosive effects

Irritating to skin and mucous membranes. Risk of serious damage to eyes. Prolonged contact with the product may cause skin disorders / chemicals burns.

### \* Sensitization

As long as material is used within shelf life sensitization is not to be expected. Refer to chapter 3+7.

## 12. Ecological information

### \* Ecotoxicity

Eco-toxicological effect only possible in case of unintended release of big quantities in contact with water due to increased pH value.

Product is slightly water pollutant (self assessment). Do not allow to enter into water courses, drains or ground water.

### \* Mobility

Refer to ecotoxicity

### \* Persistence and degradability

No data available for the preparation

### \* Bioaccumulative potential

No data available for the preparation

### \* Other adverse effects

No data available for the preparation

## 13. Disposal considerations

### Product/Preparation

#### Recommendation

Clean up dry, not contaminated material can be re-used. Hardens after contact with water, hardened material can be disposed of as *construction and demolition waste* – concrete (EWC-Code 170101). The listed waste number according to the European Waste Code (EWC) is a recommendation. The final classification has to be done together with the local waste disposal company / authority.

### Contaminated packaging

#### Recommendation

Contaminated packaging must be emptied of all residues and can be recycled following appropriate cleaning. Avoid dust formation. Uncleaned packaging must be disposed of in accordance with official local regulations (EWC-Code 150105 composite packaging (Paper/PE-foil)).

## 14. Transport information

Not a dangerous good according to the transport regulations.

## 15. Regulatory information

### Classification according to EEC directives

#### Danger symbol and danger designation

Xi irritant

#### Hazard-determining components of labelling

Cement

#### \* Risk-phrases

R 38 Irritating to skin.

R 41 Risk of serious damage to eyes

#### \* Safety-phrases

S 2 Keep out of the reach of children.

S 22 Do not breathe dust

S 24/25 Avoid contact with skin and eyes.

S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 37/39 Wear suitable gloves and eye/face protection

---

## EC Material Safety Data Sheet

Manufacturer/Supplier: Vandex Isoliermittel-Gesellschaft mbH, D-21493 Schwarzenbek  
Product number: 032  
Trade name: VANDEX ANTI SULPHATE  
Printing date: 01. 08. 2006

Reviewed on: 01. 08. 2006

Page: 4/4

---

### 16. Other information

\* Sources of key data used to compile the data sheet:

EC Directive 67/548/EC resp. 99/45/EC as amended in each case  
EC Directive 91/155/EC as amended in each case  
EC Directive 2001/58/EC as amended in each case  
EC Directive 2000/39/EC as amended in each case  
Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

\* Relevant R-phrases (chapter 2):

R 20 Harmful by inhalation  
R 25 Toxic if swallowed  
R 38 Irritating to skin  
R 41 Risk of serious damage to eyes

Alterations/supplements to the previous version are marked with \*

---

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

---